



Offering high intelligibility and natural music reproduction, CS columns are the perfect solution for highly reverberant environment such as churches, architectural spaces, auditoriums, railway stations and other transport terminals.

Based on the line array principle, the columns provide a consistent pattern control for a superior sound quality.

CS SERIES is made of plywood and is dedicated for indoor fixed installations. It is equipped with 3" full range drivers including 4 to 12 components in each box. A phoenix connector makes the connection easy to the amplification systems with rotated switch for the transformer taps selection.

Model	CS-308
Input Voltage	70V/100V
Transformer selectable power	7.5W/15W/30W/60W
System Impedance	70V-667Ω, 333Ω, 167Ω, 83Ω 100V-1333KΩ, 667Ω, 333Ω, 167Ω
Sensitivity (1W/1M)	95dB
Max SPL(1M)	115.5dB
Frequency Response (-6dB)	180Hz-18KHz
Full Range Speaker (20mm Voice Coil)	8×3"
Angle of coverage	130°x24° @4KHz

Connect	Phoneix
Enclosure Construction	Plywood cabinet, resistant paint, 0.8mm metal grille
Suspension /Mounting	8 x M8
Dimension (H x W x D)	730×98 x 130 mm (28.8" x 3.9" x 5.1")
Weight (Approx.)	7.5kg (16.54 lbs)

CS-308

[Download](#)