

- ✘
- > Supports five 10/100 Mbps adaptive ports.
- > Small and light, it is easy to carry and has multiple chips embedded in it.
- > Easy to operate.



Hardware

Included Power Adapter	Yes
Ethernet Port	5
Ethernet Port Speed	100 Mbps
Description of Function Slots	Port 1–5: 5 × 10/100 Base-T
Power Supply	5 VDC; 1 A
Operating Temperature	0 °C to +45 °C (+32 °F to +113 °F)
Operating Humidity	5%–95% (RH)
Storage Temperature	–40 °C to +70 °C (–40 °F to +158 °F)
Storage Humidity	5%–95% (RH)
Power Consumption	Idling: 0.1 W; Full load: 0.5 W
Performance	
MTBF	952.50 years
Switching Capacity	1 Gbit
Packet Forwarding Rate	0.744 Mpps
Packet Buffer Size	768 kbit
MAC Table Size	2K

General

Statics Protection	Air discharge: 8 kV Contact discharge: 4 kV
--------------------	--

Lighting Protection	Common mode: 2 kV
---------------------	-------------------

Net Weight	0.12 kg (0.26 lb)
------------	-------------------

Gross Weight	0.23 kg (0.51 lb)
--------------	-------------------

Product Dimensions	86.4 mm × 52.0 mm × 23.0 mm (3.40" × 2.05" × 0.91")
--------------------	--

Packaging Dimensions	94.0 mm × 111.0 mm × 67.0 mm (3.70" × 4.37" × 2.64")
----------------------	---

Casing Material	Plastic
-----------------	---------

Installation	Desktop mount
--------------	---------------

Certifications	CE; FCC
----------------	---------
