

- ✘
- > Supports five 10/100/1000 Mbps adaptive ports.
- > Small and light, it is easy to carry and has multiple chips embedded in it.
- > Easy to operate.
- ✘



## Technical Specifications

### Hardware

Included Power Adapter	Yes
Ethernet Port	5
Ethernet Port Speed	10/100/1000 Mbps
Description of Function Slots	Port 1-5: 5 × 10/100/1000 Base-T
Power Supply	5 VDC; 1 A
Operating Temperature	0 °C to +45 °C (+32 °F to +113 °F)
Operating Humidity	5%–95% (RH)
Storage Temperature	–40 °C to +70 °C (–40 °F to +158 °F)
Storage Humidity	5%–95% (RH)

Power Consumption	Idling: 0.5 W; Full load: 1.5 W
Performance	
MTBF	363.24 years
Switching Capacity	10 Gbit
Packet Forwarding Rate	7.44 Mpps
Packet Buffer Size	1 Mbit
MAC Table Size	2K
General	
Statics Protection	Air discharge: 8 kV Contact discharge: 4 kV
Lighting Protection	Common mode: 2 kV
Net Weight	0.12 kg (0.26 lb)
Gross Weight	0.23 kg (0.51 lb)
Product Dimensions	86.4 mm × 52.0 mm × 23.0 mm (3.40" × 2.05" × 0.91")
Packaging Dimensions	94.0 mm × 111.0 mm × 67.0 mm (3.70" × 4.37" × 2.6")
Casing Material	Plastic
Installation	Desktop mount
Certifications	CE; FCC