

## GEN-6191A06

### Network Column Speaker

The GEN-6191A06 is a wall-mounted speaker supporting DC power, SIP and VMS calls, handling 20 multicast streams and storing 20 audio files. It has priority management, timers and custom event actions via HTTP API, suitable for factories, urban construction and similar scenarios.

SIP

Onvif

Multicast



## MAIN FEATURES

### ▲ Audio Integration and Flexibility

The GEN-6191A06 supports various audio protocols, including SIP (for VoIP communication), ONVIF (for audio backchannel in video management systems), and multicast (supporting up to 20 addresses). This allows it to easily integrate with existing IP networks and various systems.

### ▲ Local audio file storage and playback

The device has built-in storage that supports up to 20 audio files (total capacity of 80MB), which can play WAV and MP3 formats. It supports various playback modes, including scheduled playback, repeat, and interval playback, making it ideal for applications such as timed announcements and emergency broadcasts.

### ▲ Easy installation and control

This speaker features a simple design and is equipped with a wall-mounted bracket, which makes the installation process quick and easy. In addition, the GEN-6191A06 supports remote control to trigger the playback function via HTTP commands or physical inputs. It includes one control input interfaces and one audio input interface, facilitating easy integration with other devices.

## SPECIFICATION

### Power Parameters

Power Supply	DC24V
Power Cons	≤3W

### Audio & Interface Parameters

Power Output	60W (Use DC 24V)
Frequency Response	100-15KHz
Sensitivity	87dB±3dB(1M/1W/1KHz)
Max SPL	102dB±3dB(1M/60W/1KHz)
SNR	≥85dB
Audio Trans	Multicast , ×20(Editable)
Audio Codec	Opus, PCMU (G.711u), PCMA (G.711a), G.722
Audio Input	×1, 500mv
Control Input	×1
Bluetooth Input	×1 ,2.4GHz
Audio Storage	Max 20 audio files ,80MB
Audio File Format	WAV, MP3

### Network Parameters

Network I/F	100BASE-TX ,RJ45 Connector
Network Protocol	TCP/IP,UDP,HTTP,RTP,RTSP ARP,ICMP,NTP,SIP,ONVIF
Config Method	Web Interface or DevConfig Tool


### Mechanical & Environment Properties

Mounting Method	Wall-Mounted
Install Env	Outdoor
Working Temp	-10°C~+55°C
Waterproof rate	IPX5
Housing Material	Aluminum alloy, iron mesh
Color	Silver Gray
Dimensions	436*140*130mm
Weight	2.56kg
Warranty	2 Years

### ACCESSORIES


1×5pin Terminal(3.5-5P)
3 × Screw(M8*14)
1 × Screw Nut(M8)
1 × Gasket(M8)
2 × Mounting Bracket
1 × Installation Manual

## INTERFACE DESCRIPTION




- ①Mic
- ②Status Light
- ③Reset Button
- ④RJ45 Connector
- ⑤Alarm Input Terminal
- ⑥Line Input Terminal
- ⑦Power Input Terminal

## CONNECTION DIAGRAM




## APPLICATION

The GEN-6191A06 Network Column Speaker supports direct SIP or VMS calls, with a built-in microphone for two-way communication. Its compact design includes IO control interfaces for camera and alarm integration, plus an audio input for display screen amplification, making it ideal for smart pole construction.



The Network Column Speaker GEN-6191A06 support Onvif protocol which can be registered to the 3-rd party monitoring system ,and during emergency situation ,the operator can directly make a live announcement to the speaker on the monitoring platform.



# INSTALLATION

unit: mm

